CM System 7.0.1
Entity Relationship Diagram

Content Engine

Item Types

PSX_OBJECTPROPERTIES

PF *	OBJECTTYPE	NUMBER (10)
P *	PROPERTYNAME	VARCHAR2 (50 BYTE)
	PROPERTYVALUE	VARCHAR2 (4000 BYTE)
	DESCRIPTION	VARCHAR2 (255 BYTE)

PK_OBJECTPROPERTIES (OBJECTTYPE, PROPERTYNAME)

PSX_OBJECTS

P *	OBJECTTYPE	NUMBER (10)
U *	OBJECTNAME	VARCHAR2 (100 BYTE)
	FACTORY	VARCHAR2 (255 BYTE)
	DESCRIPTION	VARCHAR2 (255 BYTE)
	ISWORKFLOWABLE	NUMBER (10)
*	ISREVISIONABLE	NUMBER (10)

PK_OBJECTS (OBJECTTYPE)
UNI_KEY_PSX_OBJS (OBJECTTYPE, OBJECTNAME)

Content Types

PSX_CONTENTTYPE_WORKFLOW

P *	CONTENTTYPE_WORKFLOW_ID	NUMBER (19)
*	VERSION	NUMBER (10)
	CONTENTTYPEID	NUMBER (19)
*	WORKFLOWID	NUMBER (10)

PK_PSX_CONTENTTYPE_WORKFLOW (CONTENTTYPE_WORKFLOW_ID)
IX_CTWF_WORKFLOWID (WORKFLOWID)
IX_CTWF_CONTENTTYPEID (CONTENTTYPEID)

RXLOOKUP

P *	LOOKUPID	NUMBER (10)
	LOOKUPTYPE	VARCHAR2 (50 BYTE)
	LOOKUPVALUE	VARCHAR2 (2100 BYTE)
	LOOKUPDISPLAY	VARCHAR2 (100 BYTE)
	LOOKUPSEQUENCE	NUMBER (10)
	DESCRIPTION	VARCHAR2 (255 BYTE)
*	VERSION	NUMBER (10)

PK_RXLOOKUP (LOOKUPID)
IX_RXLOOKUP_TYPE (LOOKUPTYPE)

CONTENTTYPES

P *	CONTENTTYPEID	NUMBER (19)
*	VERSION	NUMBER (10)
	CONTENTTYPENEWREQUEST	VARCHAR2 (255 BYTE)
	CONTENTTYPEQUERYREQUEST	VARCHAR2 (255 BYTE)
U *	CONTENTTYPENAME	VARCHAR2 (50 BYTE)
	CONTENTTYPELABEL	VARCHAR2 (255 BYTE)
	CONTENTTYPEDESC	VARCHAR2 (255 BYTE)
	CONTENTTYPEUPDATEREQUEST	VARCHAR2 (255 BYTE)
	HIDEFROMMENU	NUMBER (10)
*	OBJECTTYPE	NUMBER (10)

PK_CONTENTTYPES (CONTENTTYPEID)
UNI_KEY_CTYPES (CONTENTTYPENAME)

PSX_CONTENTTYPE_TEMPLATE

P *	TEMPLATE_TYPE_ID	NUMBER (19)
*	VERSION	NUMBER (10)
F	CONTENTTYPEID	NUMBER (19)
F *	TEMPLATE_ID	NUMBER (19)

PK_PSX_CONTENTTYPE_TEMPLATE (TEMPLATE_TYPE_ID)
IX_CTT_TEMPLATEID (TEMPLATE_ID)
IX_CTT_TYPEID (CONTENTTYPEID)

Folders

PSX_OBJECTACL

*	CONTENTID	NUMBER (10)
*	REVISIONID	NUMBER (10)
P *	SYSID	NUMBER (10)
*	TYPE	NUMBER (10)
*	NAME	VARCHAR2 (255 BYTE)
*	PERMISSIONS	NUMBER (10)

PK_PSX_OBJECTACL (SYSID)
IX_OBJACL_CID (CONTENTID)

PSX_FOLDER

P *	CONTENTID	NUMBER (10)
P *	REVISIONID	NUMBER (10)
	DESCRIPTION	VARCHAR2 (255 BYTE)

PK_FOLDER (CONTENTID, REVISIONID)

PSX_OBJECTPROPERTIES

PF *	OBJECTTYPE	NUMBER (10)
P *	PROPERTYNAME	VARCHAR2 (50 BYTE)
	PROPERTYVALUE	VARCHAR2 (4000 BYTE)
	DESCRIPTION	VARCHAR2 (255 BYTE)

PK_OBJECTPROPERTIES (OBJECTTYPE, PROPERTYNAME)

Content

CONTENTSTATUS

P *	CONTENTID	NUMBER (10)
	HIB_VER	NUMBER (10)
	CONTENTSTATEID	NUMBER (10)
	CONTENTCHECKOUTUSERNAME	VARCHAR2 (255 BYTE)
	CONTENTLASTMODIFIER	VARCHAR2 (255 BYTE)
	CONTENTLASTMODIFIEDDATE	DATE
	CONTENTTYPEID	NUMBER (19)
	CONTENTCREATEDDATE	DATE
	LASTTRANSITIONDATE	DATE
	NEXTAGINGDATE	DATE
	CONTENTCREATEDBY	VARCHAR2 (255 BYTE)
	CONTENTSTARTDATE	DATE
	CONTENTEXPIRYDATE	DATE
	CONTENTAGINGTIME	NUMBER (10)
	CONTENTPUBLISHDATE	DATE
	CONTENTPATHNAME	VARCHAR2 (255 BYTE)
	CONTENTSUFFIX	VARCHAR2 (50 BYTE)
*	WORKFLOWAPPID	NUMBER (10)
	TITLE	VARCHAR2 (255 BYTE)
	CURRENTREVISION	NUMBER (10)
	TIPREVISION	NUMBER (10)
	EDITREVISION	NUMBER (10)
	REVISIONLOCK	CHAR (1 BYTE)
	CLONEDPARENT	NUMBER (10)
	REMINDERDATE	DATE
	STATEENTEREDDATE	DATE
	NEXTAGINGTRANSITION	NUMBER (10)
	REPEATEDAGINGTRANSSTARTDATE	DATE
	COMMUNITYID	NUMBER (10)
	LOCALE	VARCHAR2 (16 BYTE)
*	OBJECTTYPE	NUMBER (10)
	PUBLIC_REVISION	NUMBER (10)

PK_CONTENTSTATUS (CONTENTID)
IX_CONSTAT_TITLE (TITLE)
IX_CONSTAT_AUTH (CONTENTCREATEDBY)
IX_CONSTAT_USER (CONTENTCHECKOUTUSERNAME)

CONTENTSTATUSHISTORY

P *	CONTENTSTATUSHISTORYID	NUMBER (10)
*	CONTENTID	NUMBER (10)
	REVISIONID	NUMBER (10)
	SESSIONID	CHAR (40 BYTE)
	ACTOR	VARCHAR2 (255 BYTE)
	VALID	CHAR (1 BYTE)
	STATEID	NUMBER (10)
	TRANSITIONID	NUMBER (10)
	ROLENAME	VARCHAR2 (255 BYTE)
	STATENAME	VARCHAR2 (50 BYTE)
	TRANSITIONLABEL	VARCHAR2 (50 BYTE)
	CHECKOUTUSERNAME	VARCHAR2 (255 BYTE)
	LASTMODIFIERNAME	VARCHAR2 (255 BYTE)
	LASTMODIFIEDDATE	DATE
	EVENTTIME	DATE
*	WORKFLOWAPPID	NUMBER (10)
	TITLE	VARCHAR2 (500 BYTE)
	TRANSITIONCOMMENT	VARCHAR2 (255 BYTE)

PK_CSTATUSHISTORY (CONTENTSTATUSHISTORYID)
IX_CONHIS_CONID (CONTENTID)

Internationalization

PSX_AUTOTRANSLATION

P *	CONTENTTYPEID	NUMBER (19)
P *	LOCALE	VARCHAR2 (16 BYTE)
*	COMMUNITYID	NUMBER (10)
*	WORKFLOWID	NUMBER (10)
*	VERSION	NUMBER (10)

PK_PSX_AUTOTRANSLATION (CONTENTTYPEID, LOCALE)

RXLOCALEPROPERTY

P *	LOCALEID	NUMBER (10)
P *	PROPERTYNAME	VARCHAR2 (50 BYTE)
	PROPERTYVALUE	VARCHAR2 (50 BYTE)
	DESCRIPTION	VARCHAR2 (255 BYTE)

PK_LOCALEPROPERTY (LOCALEID, PROPERTYNAME)

RXLOCALE

P *	LOCALEID	NUMBER (10)
*	LANGUAGESTRING	VARCHAR2 (16 BYTE)
*	DISPLAYNAME	VARCHAR2 (50 BYTE)
	SORTORDER	NUMBER (10)
	DESCRIPTION	VARCHAR2 (255 BYTE)
	STATUS	NUMBER (10)
*	VERSION	NUMBER (10)

PK_RXLOCALE (LOCALEID)

Assembly Engine

Templates

PSX_TEMPLATE_BINDING

P *	BINDING_ID	NUMBER (19)
*	VERSION	NUMBER (10)
	EXECUTION_ORDER	NUMBER (10)
F	TEMPLATE_ID	NUMBER (19)
	VARIABLE	VARCHAR2 (64 BYTE)
*	EXPRESSION	CLOB

PK_PSX_TEMPLATE_BINDING (BINDING_ID)

PSX_TEMPLATE

P *	TEMPLATE_ID	NUMBER (19)
*	VERSION	NUMBER (10)
	LABEL	VARCHAR2 (100 BYTE)
	NAME	VARCHAR2 (100 BYTE)
	STYLESHEETNAME	VARCHAR2 (100 BYTE)
	ASSEMBLYURL	VARCHAR2 (2100 BYTE)
	ASSEMBLER	VARCHAR2 (256 BYTE)
	OUTPUTFORMAT	NUMBER (10)
	AATYPE	NUMBER (10)
	TEMPLATE_TYPE	NUMBER (10)
	DESCRIPTION	VARCHAR2 (255 BYTE)
	PUBLISHWHEN	CHAR (1 BYTE)
	LOCATIONPREFIX	VARCHAR2 (10 BYTE)
	LOCATIONSUFFIX	VARCHAR2 (10 BYTE)
	TEMPLATE	CLOB
	MIME_TYPE	VARCHAR2 (64 BYTE)
	CHARSET	VARCHAR2 (64 BYTE)
	GLOBAL_TEMPLATE_USAGE	NUMBER (10)
	GLOBAL_TEMPLATE	NUMBER (19)

PK_PSX_TEMPLATE (TEMPLATE_ID)
IX_TEMPLATE_NAME (NAME)

RXSLOTCONTENT

P *	SLOTID	NUMBER (19)
*	VERSION	NUMBER (10)
P *	CONTENTTYPEID	NUMBER (19)
P *	VARIANTID	NUMBER (19)

PK_RXSLOTCONTENT (SLOTID, CONTENTTYPEID, VARIANTID)
IX_SLOTCON_CID_VID (CONTENTTYPEID, VARIANTID)

PSX_VARIANT_SITE

P *	VARIANTID	NUMBER (19)
P *	SITEID	NUMBER (19)

PK_PSX_VARIANT_SITE (VARIANTID, SITEID)

RXVARIANTSLOTTYPE

P *	VARIANTID	NUMBER (19)
P *	SLOTID	NUMBER (19)

PK_RXVARIANTSLOTTYPE (VARIANTID, SLOTID)
IX_VARSLOTTYPE_SID (SLOTID)

Item Filters

PSX_ITEM_FILTER_RULE_PARAM

P *	FILTER_RULE_PARAM_ID	NUMBER (19)
F	FILTER_RULE_ID	NUMBER (19)
*	VERSION	NUMBER (10)
	NAME	VARCHAR2 (64 BYTE)
*	VALUE	VARCHAR2 (256 BYTE)

PK_PSX_ITEM_FILTER_RULE_PARAM (FILTER_RULE_PARAM_ID)

PSX_ITEM_FILTER_RULE

P *	FILTER_RULE_ID	NUMBER (19)
*	VERSION	NUMBER (10)
F *	FILTER_ID	NUMBER (19)
*	NAME	VARCHAR2 (256 BYTE)

PK_PSX_ITEM_FILTER_RULE (FILTER_RULE_ID)

PSX_ITEM_FILTER

P *	FILTER_ID	NUMBER (19)
*	VERSION	NUMBER (10)
	PARENT_FILTER_ID	NUMBER (19)
*	NAME	VARCHAR2 (64 BYTE)
	DESCRIPTION	VARCHAR2 (1023 BYTE)
	LEGACY_AUTHTYPE	NUMBER (10)

PK_PSX_ITEM_FILTER (FILTER_ID)

Slots

PSX_SLOT_FINDER_PARAM

P *	PARAM_ID	NUMBER (19)
*	VERSION	NUMBER (10)
*	NAME	VARCHAR2 (64 BYTE)
*	VALUE	VARCHAR2 (1023 BYTE)
F	SLOTID	NUMBER (19)

PK_SLOTFINDERPARAM (PARAM_ID)

RXSLOTTYPE

P *	SLOTID	NUMBER (19)
*	VERSION	NUMBER (10)
	LABEL	VARCHAR2 (100 BYTE)
	SLOTNAME	VARCHAR2 (100 BYTE)
	SLOTDESC	VARCHAR2 (255 BYTE)
	SYSTEMSLOT	NUMBER (10)
	SLOTTYPE	NUMBER (10)
	RELATIONSHIPNAME	VARCHAR2 (50 BYTE)
	FINDER	VARCHAR2 (1023 BYTE)

PK_RXSLOTTYPE (SLOTID)
IX_SLOTTYPE_NAME (SLOTNAME)

Workflow Engine

TRANSITIONROLES

PF *	TRANSITIONID	NUMBER (10)
PF *	WORKFLOWAPPID	NUMBER (10)
P *	TRANSITIONROLEID	NUMBER (10)

PK_TRANSITIONROLES (TRANSITIONID, WORKFLOWAPPID, TRANSITIONROLEID)
IX_TROLES_WID_RID (WORKFLOWAPPID, TRANSITIONROLEID)

STATEROLES

P *	STATEID	NUMBER (10)
P *	ROLEID	NUMBER (10)
	ASSIGNMENTTYPE	NUMBER (10)
	ADHOCTYPE	NUMBER (10)
	ISNOTIFYON	CHAR (1 BYTE)
P *	WORKFLOWAPPID	NUMBER (10)
*	SHOWININBOX	CHAR (1 BYTE)

PK_STATEROLES (STATEID, ROLEID, WORKFLOWAPPID)
IX_STROLES_WID_SID (WORKFLOWAPPID, STATEID)

STATES

P *	STATEID	NUMBER (10)
*	STATENAME	VARCHAR2 (50 BYTE)
*	CONTENTVALID	CHAR (1 BYTE)
	STATEDESC	VARCHAR2 (255 BYTE)
P *	WORKFLOWAPPID	NUMBER (10)
	SORTORDER	NUMBER (10)

PK_STATES (STATEID, WORKFLOWAPPID)
IX_STATES_NAME (STATENAME)

TRANSITIONS

P *	TRANSITIONID	NUMBER (10)
	TRANSITIONTYPE	NUMBER (10)
	TRANSITIONLABEL	VARCHAR2 (50 BYTE)
	TRANSITIONPROMPT	VARCHAR2 (50 BYTE)
	TRANSITIONFROMSTATEID	NUMBER (10)
	TRANSITIONTOSTATEID	NUMBER (10)
	TRANSITIONACTIONTRIGGER	VARCHAR2 (50 BYTE)
	TRANSITIONAPPROVALSREQUIRED	NUMBER (10)
	TRANSITIONDESC	VARCHAR2 (255 BYTE)
P *	WORKFLOWAPPID	NUMBER (10)
	TRANSITIONACTIONS	VARCHAR2 (255 BYTE)
	TRANSITIONROLES	VARCHAR2 (255 BYTE)
	TRANSITIONCOMMENTREQUIRED	CHAR (1 BYTE)
	AGINGTYPE	NUMBER (10)
	AGINGINTERVAL	NUMBER (10)
	SYSTEMFIELD	VARCHAR2 (50 BYTE)
	DEFAULTTRANSITION	CHAR (1 BYTE)

PK_TRANSITIONS (TRANSITIONID, WORKFLOWAPPID)

TRANSITIONNOTIFICATIONS

P *	TRANSITIONNOTIFICATIONID	NUMBER (10)
*	TRANSITIONID	NUMBER (10)
*	NOTIFICATIONID	NUMBER (10)
	STATEROLERECIPIENTTYPES	NUMBER (10)
	ADDITIONALRECIPIENTLIST	VARCHAR2 (255 BYTE)
	CCLIST	VARCHAR2 (255 BYTE)
P *	WORKFLOWAPPID	NUMBER (10)

PK_TRANSITIONNOTIFICATIONS (WORKFLOWAPPID, TRANSITIONNOTIFICATIONID)
IX_TNTIF_WID_TID (WORKFLOWAPPID, TRANSITIONID)

WORKFLOWAPPS

P *	WORKFLOWAPPID	NUMBER (10)
*	WORKFLOWAPPNAME	VARCHAR2 (50 BYTE)
	ADMINISTRATOR	VARCHAR2 (50 BYTE)
	INITALSTATEID	NUMBER (10)
	WORKFLOWAPPDESC	VARCHAR2 (255 BYTE)
	VERSION	NUMBER (10)

PK_WORKFLOWAPPS (WORKFLOWAPPID)

CONTENTADHOCUSERS

P *	CONTENTID	NUMBER (10)
P *	USERNAME	VARCHAR2 (50 BYTE)
	ADHOCTYPE	NUMBER (10)
P *	ROLEID	NUMBER (10)

PK_ADHOCUSERS (CONTENTID, ROLEID, USERNAME)

ROLES

P *	ROLEID	NUMBER (10)
*	ROLENAME	VARCHAR2 (50 BYTE)
	ROLEDESC	VARCHAR2 (255 BYTE)
P *	WORKFLOWAPPID	NUMBER (10)

PK_ROLES (ROLEID, WORKFLOWAPPID)
IX_ROLES_WRK_NAME (WORKFLOWAPPID, ROLENAME)

CONTENTAPPROVALS

P *	CONTENTID	NUMBER (10)
	STATEID	NUMBER (10)
	TRANSITIONID	NUMBER (10)
P *	USERNAME	VARCHAR2 (50 BYTE)
P *	WORKFLOWAPPID	NUMBER (10)
	ROLEID	NUMBER (10)

PK_CONTENTAPPROVAL (CONTENTID, WORKFLOWAPPID, USERNAME)

NOTIFICATIONS

P *	NOTIFICATIONID	NUMBER (10)
	SUBJECT	VARCHAR2 (50 BYTE)
	BODY	CLOB
P *	WORKFLOWAPPID	NUMBER (10)
	DESCRIPTION	VARCHAR2 (255 BYTE)

PK_NOTIFICATIONS (NOTIFICATIONID, WORKFLOWAPPID)

Link / Path Management

RXCONTEXT

P *	CONTEXTID	NUMBER (19)
*	VERSION	NUMBER (10)
	CONTEXTNAME	VARCHAR2 (50 BYTE)
	CONTEXTDESC	VARCHAR2 (255 BYTE)
	DEFAULTSCHEMEID	NUMBER (19)

PK_RXCONTEXT (CONTEXTID)

RXLOCATIONSCHEMEPARAMS

P *	SCHEMEPARAMID	NUMBER (10)
*	SCHEMEID	NUMBER (10)
*	SEQUENCE	NUMBER (10)
*	TYPE	VARCHAR2 (50 BYTE)
*	NAME	VARCHAR2 (50 BYTE)
*	VALUE	VARCHAR2 (2100 BYTE)

PK_RXLOCATIONSCHEMEPARAMS (SCHEMEPARAMID)
IX_LOCSCHPRM_SID (SCHEMEID)

RXLOCATIONSCHEME

P *	SCHEMEID	NUMBER (19)
*	VERSION	NUMBER (10)
	SCHEMENAME	VARCHAR2 (50 BYTE)
	DESCRIPTION	VARCHAR2 (255 BYTE)
U *	VARIANTID	NUMBER (19)
U *	CONTENTTYPEID	NUMBER (19)
U *	CONTEXTID	NUMBER (19)
	GENERATOR	VARCHAR2 (255 BYTE)

PK_RXLOCATIONSCHEME (SCHEMEID)
UIX_RXLOCSCHEME (CONTEXTID, VARIANTID, CONTENTTYPEID)

RXASSEMBLERPROPERTIES

*	SITEID	NUMBER (19)
*	VERSION	NUMBER (10)
*	CONTEXTID	NUMBER (10)
P *	PROPERTYID	NUMBER (19)
	PROPERTYNAME	VARCHAR2 (50 BYTE)
	PROPERTYVALUE	VARCHAR2 (255 BYTE)

PK_RXASSEMBLERPROPERTIES (PROPERTYID)

Search

PSX_SEARCHINDEXQUEUE

P *	QUEUEID	NUMBER (10)
*	EVENT	CLOB

PK_SEARCHINDEXQUEUE (QUEUEID)

Security

Community

RXCOMMUNITY

P *	COMMUNITYID	NUMBER (10)
*	VERSION	NUMBER (10)
*	NAME	VARCHAR2 (50 BYTE)
	DESCRIPTION	VARCHAR2 (255 BYTE)

PK_RXCOMMUNITY (COMMUNITYID)
IX_COMMUNITY_NAME (NAME)

RXCOMMUNITYROLE

P *	ROLEID	NUMBER (10)
P *	COMMUNITYID	NUMBER (10)

PK_RXCOMMUNITYROLE (ROLEID, COMMUNITYID)
IX_COMITYROL_CID (COMMUNITYID)

RXCOMPONENTCOMMUNITY

P *	COMPONENTID	NUMBER (10)
P *	COMMUNITYID	NUMBER (10)

PK_COMPONENTCOMMUN (COMPONENTID, COMMUNITYID)
IX_COMPCOMITY_CID (COMMUNITYID)

ACLs

PSX_ACLENTRYPERMISSIONS

P *	ID	NUMBER (19)
F *	ENTRYID	NUMBER (19)
*	PERMISSION	NUMBER (10)

PK_PSX_ACLENTRYPERMISSIONS (ID)
IDX_ACL_PERM2 (ENTRYID, PERMISSION)

PSX_ACLENTRIES

P *	ID	NUMBER (19)
F *	ACLID	NUMBER (19)
*	NAME	VARCHAR2 (50 BYTE)
	DESCRIPTION	VARCHAR2 (255 BYTE)
*	TYPE	NUMBER (10)

PK_PSX_ACLENTRIES (ID)
IX_ENTRY_NAME_TYPE (NAME, TYPE)
IX_ENTRY_TYPE_NAME (TYPE, NAME)
IDX_ACLENTRY_ACLID (ACLID)

PSX_ACLS

P *	ID	NUMBER (19)
*	OBJECTTYPE	NUMBER (10)
*	OBJECTID	NUMBER (19)
*	NAME	VARCHAR2 (50 BYTE)
	DESCRIPTION	VARCHAR2 (255 BYTE)
*	VERSION	NUMBER (10)

PK_PSX_ACLS (ID)
IDX_ACL_TYPE_ID (OBJECTID, OBJECTTYPE)

Backend Table Security Provider

USERLOGIN

P *	USERID	VARCHAR2 (50 BYTE)
	PASSWORD	VARCHAR2 (50 BYTE)

PK_USERLOGIN (USERID)

PSX_ROLES

P *	ID	NUMBER (10)
*	NAME	VARCHAR2 (50 BYTE)
	COMPONENTID	NUMBER (10)
*	NORMALNAME	VARCHAR2 (50 BYTE)

PK_PSX_ROLES (ID)
IX_ROLES_NNAME (NORMALNAME)

Publishing Engine

Editions

RXEDITION

P *	EDITIONID	NUMBER (19)
*	VERSION	NUMBER (10)
	DISPLAYTITLE	VARCHAR2 (100 BYTE)
	EDITIONCOMMENT	VARCHAR2 (255 BYTE)
	EDITIONTYPE	VARCHAR2 (100 BYTE)
	DESTSITE	NUMBER (19)
	PRIORITY	NUMBER (10)

PK_RXEDITION (EDITIONID)

RXEDITIONCLIST

P *	EDITIONCLISTID	NUMBER (19)
P *	EDITIONID	NUMBER (19)
P *	CONTENTLISTID	NUMBER (19)
	SEQUENCE	NUMBER (10)
	AUTHTYPE	NUMBER (10)
*	CONTEXT	NUMBER (10)
	ASSEMBLY_CONTEXT	NUMBER (10)

PK_RXEDITIONCLIST (EDITIONCLISTID, EDITIONID, CONTENTLISTID)
IX_EDLIST_EDN_LIST (EDITIONID, CONTENTLISTID)

PSX_EDITION_TASK

P *	TASK_ID	NUMBER (19)
*	VERSION	NUMBER (10)
*	EDITION_ID	NUMBER (19)
*	SEQUENCE	NUMBER (10)
*	EXTENSION_NAME	VARCHAR2 (1024 BYTE)
*	CONTINUE_ON_FAILURE	NUMBER (3)

PK_PSX_EDITION_TASK (TASK_ID)
IX_EDITION_FK (EDITION_ID)

PSX_EDITION_TASK_LOG

P *	REFERENCE_ID	NUMBER (19)
*	VERSION	NUMBER (10)
*	JOB_ID	NUMBER (19)
*	STATUS	NUMBER (3)
	ELAPSED	NUMBER (10)
*	TASK_ID	NUMBER (19)
	MESSAGE	CLOB

PK_PSX_EDITION_TASK_LOG (REFERENCE_ID)
IX_EDTN_TSK_LG_JID (JOB_ID)

PSX_EDITION_TASK_PARAM

P *	TASK_PARAM_ID	NUMBER (19)
*	VERSION	NUMBER (10)
	TASK_ID	NUMBER (19)
*	NAME	VARCHAR2 (255 BYTE)
	VALUE	VARCHAR2 (2048 BYTE)

PK_PSX_EDITION_TASK_PARAM (TASK_PARAM_ID)
IX_EDITION_TASK_FK (TASK_ID)

Content Lists

PSX_CONTENTLIST_EXPANDER_PARAM

P *	PARAM_ID	NUMBER (19)
F	CONTENT_LIST_ID	NUMBER (19)
*	VERSION	NUMBER (10)
	NAME	VARCHAR2 (64 BYTE)
*	VALUE	VARCHAR2 (4000 BYTE)

SYS_C0012667 (PARAM_ID)
IX_SYS_C0012667 (PARAM_ID)

RXCONTENTLIST

P *	CONTENTLISTID	NUMBER (19)
*	VERSION	NUMBER (10)
U *	NAME	VARCHAR2 (100 BYTE)
	DESCRIPTION	VARCHAR2 (255 BYTE)
*	TYPE	NUMBER (5)
	URL	VARCHAR2 (2100 BYTE)
	EDITIONTYPE	VARCHAR2 (100 BYTE)
	GENERATOR	VARCHAR2 (256 BYTE)
	EXPANDER	VARCHAR2 (256 BYTE)
	FILTER_ID	NUMBER (19)

PK_RXCONTENTLIST (CONTENTLISTID)
IX_CONLIST_NAME (NAME)
IX_CONLIST_EDN (EDITIONTYPE)

PSX_CONTENTLIST_GEN_PARAM

P *	PARAM_ID	NUMBER (19)
F	CONTENT_LIST_ID	NUMBER (19)
*	VERSION	NUMBER (10)
	NAME	VARCHAR2 (64 BYTE)
*	VALUE	VARCHAR2 (4000 BYTE)

PK_PSX_CONTENTLIST_GEN_PARAM (PARAM_ID)

Publication Logging

PSX_PUBLICATION_SITE_ITEM

PF *	REFERENCE_ID	NUMBER (19)
*	VERSION	NUMBER (10)
*	SITE_ID	NUMBER (19)
*	CONTEXT_ID	NUMBER (10)
	UNPUBLISH_INFO	BLOB

PK_PSX_PUBLICATION_SITE_ITEM (REFERENCE_ID)
IX_SITE_ITEMS (SITE_ID, CONTEXT_ID)

PSX_PUBLICATION_DOC

P *	REFERENCE_ID	NUMBER (19)
*	VERSION	NUMBER (10)
F	STATUS_ID	NUMBER (19)
*	CONTENT_ID	NUMBER (10)
	REVISION_ID	NUMBER (10)
	FOLDER_ID	NUMBER (10)
	TEMPLATE_ID	NUMBER (19)
	LOCATION	VARCHAR2 (2100 BYTE)
	PUBLISHING_DATE	DATE
	OPERATION	NUMBER (3)
	ASSEMBLY_URL	VARCHAR2 (2100 BYTE)
	ELAPSED	NUMBER (10)
	STATUS	NUMBER (3)
	HIDDEN	CHAR (1 BYTE)
	PAGE	NUMBER (10)
	PAGE_REFERENCE_ID	NUMBER (19)
	DELIVERY_TYPE	VARCHAR2 (80 BYTE)
	MESSAGE	CLOB
	UNPUBLISH_REF_ID	NUMBER (19)

PK_PSX_PUBLICATION_DOC (REFERENCE_ID)
IX_PBDOCS_PBSTATUS (STATUS_ID)
IX_PUBDOCS_LOOKUP (CONTENT_ID, REVISION_ID, FOLDER_ID, TEMPLATE_ID, PAGE)

PSX_PUBLICATION_STATUS

P *	STATUS_ID	NUMBER (19)
*	VERSION	NUMBER (10)
	START_DATE	DATE
	END_DATE	DATE
*	EDITION_ID	NUMBER (19)
	ENDING_STATUS	NUMBER (10)
*	DELIVERED_COUNT	NUMBER (10)
*	REMOVED_COUNT	NUMBER (10)
*	FAILED_COUNT	NUMBER (10)
	HIDDEN	CHAR (1 BYTE)
	SERVER	VARCHAR2 (255 BYTE)

PK_PSX_PUBLICATION_STATUS (STATUS_ID)

RXEDITIONITEM

P *	EDITIONID	NUMBER (10)
P *	CONTENTID	NUMBER (10)
	REVISION	NUMBER (10)
	VARIANT	NUMBER (10)
	PUBSTATUS	VARCHAR2 (25 BYTE)
	PUBTYPE	NUMBER (10)

PK_RXEDITIONITEM (CONTENTID, EDITIONID)

Delivery Handlers

PSX_DELIVERY_TYPE

P *	ID	NUMBER (19)
U *	NAME	VARCHAR2 (50 BYTE)
	DESCRIPTION	VARCHAR2 (255 BYTE)
	BEAN_NAME	VARCHAR2 (255 BYTE)
*	UNPUBLISHING_REQUIRES_ASSEMBLY	NUMBER (10)

PK_PSX_DELIVERY_TYPE (ID)
IX_DELIVERY_TYP_NM (NAME)

Relationship Engine

PSX_OBJECTRELATIONSHIPPROP

PF *	RID	NUMBER (10)
P *	PROPERTYNAME	VARCHAR2 (50 BYTE)
	PROPERTYVALUE	VARCHAR2 (255 BYTE)

PK_OBJECTRELATIONSHIPPROP (RID, PROPERTYNAME)

PSX_OBJECTRELATIONSHIP

P *	RID	NUMBER (10)
F *	CONFIG_ID	NUMBER (10)
*	OWNER_ID	NUMBER (10)
	OWNER_REVISION	NUMBER (10)
*	DEPENDENT_ID	NUMBER (10)
	DEPENDENT_REVISION	NUMBER (10)
	SLOT_ID	NUMBER (19)
	SORT_RANK	NUMBER (10)
	VARIANT_ID	NUMBER (19)
	FOLDER_ID	NUMBER (10)
	SITE_ID	NUMBER (19)
	INLINE_RELATIONSHIP	VARCHAR2 (255 BYTE)

PK_OBJECTRELATIONSHIP (RID)
IX_RLNSHIP_DEPID (DEPENDENT_ID)
IX_RLNSHIP_OWNERID (OWNER_ID)
IX_RLNSHIP_SLOTID (SLOT_ID)

PSX_RELATIONSHIPCONFIGNAME

P *	CONFIG_ID	NUMBER (10)
*	CONFIG_NAME	VARCHAR2 (255 BYTE)
*	VERSION	NUMBER (10)

PK_RELATIONSHIPCONFIGNAMES (CONFIG_ID)

Sites

RXSITES

P *	SITEID	NUMBER (19)
*	VERSION	NUMBER (10)
	SITENAME	VARCHAR2 (100 BYTE)
	SITEDESC	VARCHAR2 (255 BYTE)
	BASEURL	VARCHAR2 (2100 BYTE)
	ROOT	VARCHAR2 (128 BYTE)
	UNPUBLISH_FLAGS	VARCHAR2 (50 BYTE)
	IPADDRESS	VARCHAR2 (50 BYTE)
	PORT	NUMBER (10)
	USERID	VARCHAR2 (50 BYTE)
	PASSWORD	VARCHAR2 (50 BYTE)
	STATE	NUMBER (10)
	FOLDER_ROOT	VARCHAR2 (2100 BYTE)
	NAV_THEME	VARCHAR2 (50 BYTE)
	GLOBALTEMPLATE	VARCHAR2 (100 BYTE)
	ALLOWED_NAMESPACES	VARCHAR2 (256 BYTE)

PK_RXSITES (SITEID)

percussion®